

9575A DOCKING STATION









SECURE DOCKING
STATION FOR THE
IRIDIUM 9575A
SATELLITE PHONE

*Shown with optional handset

- Secure sleeve docking cradle with POTS support
- Small profile solution with wall mounting
- Optional external antenna for Iridium and GPS capabilities
- DOD compatibility with Iridium Security Module 2
- AC/DC adapter
- Simple set-up and troubleshooting
- · 24/7 global customer support

ENCRYPTED SATELLITE COMMUNICATIONS SOLUTION

The 9575A Docking Station is the only docking station that supports General Dynamics' Iridium 9575A satellite phone handset. It is the ideal secure satellite communications solution for your military/government operations, no matter where you are. It works with General Dynamics' DOD security module 2 and Enhanced Mobile Satellite Services (EMSS) for global voice, data, and paging capabilities. The docking station also enables easy integration into your existing Plain Ordinary Telephone Service (POTS). Its small form factor and easy wall mounting make for easy integration into your spaces.



WHAT'S IN THE BOX



ASE-9575A-HQ-DOD

CONTENTS:

- > Secure sleve docking cradle with POTS support
- > Wall mount bracket
- > AC/DC adapter



ASE-9575A-HQ-DOD-H

- > Adds ASE-MNT11
- > Adds ASF-PS06

SPECIFICATIONS

- **OPERATING VOLTAGE: 10 32 VDC**
- POWER CONSUMPTION: 12 watts (active peak)
- AC MAINS: 115/230 VAC 50/60Hz to 12 VDC; adapter provided
- ANTENNA CONNECTIONS: Iridium TNC-F; GPS SMA-F
- **OPERATING TEMP RANGE:** 14°F to 131°F / -10°C to 55°C
- **EXPOSURE:** Indoor
- **DIMENSIONS:** 13 x 6 x 4.5 in. / 33 x 15 x 11.5 cm
- **SHIPPING DIMENSIONS:** 16 x 14 x 8 in. / 41 x 36 x 20 cm
- **WEIGHT:** 3.5 lbs. / 1.6 kg
- SHIPPING WEIGHT: 6 lbs. / 2.7 kg
- **MOUNTING:** Swivel desk or wall mount available

OPTIONAL ACCESSORIES



ASE-DA12 / ASE-DA20 External antenna Iridium/GPS



ASE-FA12 / ASE-FA20 External antenna Iridium only*



ASE-PT01 POTS phone and mount



ASE-MNT11 Privacy handset and swivel mount



ASE-PS06 Vehicle power adapter

*No GPS features supported



























ASE 9575A TOC BOX



AN ALL-IN-ONE,
GRAB-AND-GO
SATELLITE

COMMUNICATIONS KIT

*Shown with 9575A (not included)

ASE-9575A-TOC

A rugged, grab-and-go 9575A communications kit

- · Tough, military grade design
- 9575A battery life up to 15 hours, 2 hours talk time
- 100% global coverage, including the poles
- Ruggedized Pelican case stores all accessories
- DOD compatibility with Iridium Security Module 2
- Simple set-up and troubleshooting
- 24/7 global customer support

TACTICAL OPERATIONS CENTER - INFORMED BY THE FRONTLINE OPERATOR

The TOC Box was made with only one thing in mind: the operator. For nearly 20 years, Blue Sky Network has been making quality satellite communications equipment and solutions for government and military applications. Our customers operate in some of the most remote environments, extreme temperatures, and hostile areas in the world.

INTEGRATE YOUR 9575A

The 9575A satellite phone offers unmatched pole-to-pole coverage and a rugged, ergonomic design for the most demanding government and military customers.

Blue Sky Network offers the full 9575A TOC Box Kit. We can also integrate your existing 9575A satellite phone, or other custom Internet of Things (IoT) requirements, into our case.



WHAT'S IN THE BOX



ASE-9575A-HQ-DOD DOCKING STATION

The only docking station that supports General Dynamics' Iridium 9575A satellite phone handset.

*9575A not included



PRIVACY HANDSET

Shows system status info and provides a convenient interface for calls when in close proximity to the docking station.



ASE-FA12 / ASE-FA20

Passive, external, fixed-mount Iridium antenna that allows up to 20 meters of cable run.



33' COAX CABLE

LMR400 RF cable with TNC male connectors.

SPECIFICATIONS

- **OPERATING VOLTAGE: 10 32 VDC**
- POWER CONSUMPTION: 12 watts (active peak)
- AC MAINS: 115/230 VAC 50/60Hz to 24 VDC; adapter provided
- ANTENNA CONNECTIONS: Iridium TNC-F; GPS SMA-F
- **OPERATING TEMP RANGE:** 14°F to 131°F / -10°C to 55°C
- **DIMENSIONS:** 20.66 x 17.20 x 8.40 in / 52.5 x 43.7 x 21.3 cm
- **WEIGHT:** 16.4 lbs / 7.4 kg
- PORTABLE: Ships USPS, FedEx, or in-flight luggage

USE CASES:

Forward operating bases, Mission-critical comms, Top Secret encrypted calls

ISO 9001:2015 AND A9100D CERTIFIED





















