

SRV[®] EXTREME 3x

Custom Built EOD DR Imager

- Latest Non-Glass DR Technology
- Narrow 4mm Margin
- EOD Rugged 4 Ft. Drop Tested + IP67
- Picatinny mounting system with rugged bipod and carrying handle
- Temperature Range -21°F to 150°F

Advanced Communications Hardware & Software

- Real-Time Power & WiFi SitRep
- RF Spectrum Certified
- Host Nation Compliance
- Comms Frequency of 5GHz
- Self Healing WiFi
- Military (STIGS) Cyber Secure

Component List

- Near Zero Margin DR Imager Panel (IP67)
- Mil-Grade Controller (IP65)
- Compact CommTrigger[®] (IP65) with Picatinny mount
- Bipod and Carrying Handle
- (2) 6 meter ultrathin network cable spool
- (1) 50 meter ultrathin network cable spool
- All New SRV[®] Software with Reachback
- Custom Ruggedized Case

*Systems include batteries and other small accessories

Complete System Options

- SRV X1012[®] Extreme 3x
- SRV X1417[®] Extreme 3x
- SRV[®] Dual Extreme 3X

*X-Ray Generator sold separately



SmartRayVision[®]

Always in the Clear

877.638.3868 | sales@smartrayvision.com

