

StreamCaster LITE 4200

2x2 MIMO Radio

50% THINNER* | 30% LIGHTER*

...100% SILVUS



SILVUS
TECHNOLOGIES

LEADING THE MIMO REVOLUTION

*Compared to SC4200

STREAMCASTER LITE



GENERAL

WAVEFORM	Mobile Networked MIMO (MN-MIMO)
ENCRYPTION	DES56 (Standard) AES256 (Optional)
DATA RATE	Up to 20Mbps (Adaptive)
MIMO TECHNIQUES	Spatial Multiplexing, Space-Time Coding, TX/RX Eigen Beamforming
OUTPUT POWER	1mW - 1W variable (up to 2W effective w/TX Beamforming)
LATENCY	28ms average (5MHz BW)
SENSITIVITY	-105dBm @ 1.25MHz BW
CHANNEL BANDWIDTH	1.25, 2.5, or 5 MHz
DIAGNOSTICS	Spectrum Scanning, Statistics Logging, Temperature/Voltage Monitoring

POWER

VOLTAGE	8-32 VDC or USB-PD (9V@3A min)
POWER CONSUMPTION	4.8W-17W @ 1W TX Power

MECHANICAL

AMBIENT TEMPERATURE	-40° to +65° C
IP RATING	IP67 (Up to 1m for 30min)
DIMENSIONS	140 x 72 x 20 mm (with connectors)
WEIGHT	295 grams
MATERIAL	Black Anodized Aluminum

INTERFACES

RF	2x TNC(f)
DATA	1x USB 2.0 Host; 1x USB 2.0 OTG; 1x Serial RS-232
CONNECTOR	Proprietary 20-pin side-connector
STATUS INDICATOR	Bi-Color LED
CONTROL INTERFACE	2-Position ON/OFF Switch Web-Based StreamScape Network Manager

FREQUENCY BAND OPTIONS

(all bands listed in MHz)

<u>BAND</u>	<u>RANGE</u>	<u>BAND</u>	<u>RANGE</u>
L Band (139) *	1350 - 1440	Federal C-1 (467)	4400-4940
S Band (235)	2200-2500		

* In development

MECHANICAL - OEM VERSION

(shown below)

DIMENSIONS	97 x 70 x 11.3 mm
WEIGHT	105 grams
I/O CONNECTORS	Qty 6, Molex style (Power, data, status, control)
RF CONNECTORS	2x SMP (m)

